
L.F
Group
NEW!
KLARCO
p. 2-12
RdF
rubinetterie del friuli
p. 14-29
Water faucets
100%
Made in Italy
2017

KLARCO®

p. 3 Docce prelavaggio
Pre-rinse units
Waschbrausen & Zubehör
Duchas pre-lavado



3759322

GRUPPO DOCCIA SHRINK KL H.60 NERO

comando leva lunga 220 mm
canna ø 25 x 175 mm
doccia BEST versione PRO
attacchi ø 3/8" F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata 60°c

SHOWER GROUP SHRINK KL H.60 BLACK

long lever control 220 mm
spout ø 25x175 mm
shower BEST version PRO
fittings ø 3/8" F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK KL H.60 SCHWARZ

lange Hebelbedienung 220 mm
Rohr ø 25 x 175 mm
Dusche BEST Mod. PRO
Anschlüsse ø 3/8" F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60°c

GRUPO DUCHA SHRINK KL H.60 NEGRO

mando con palanca larga 220 mm
caño ø 25 x 175 mm
ducha BEST versión PRO
conexiones ø 3/8" F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max 10 bar
temperatura max 90°c aconsejada 60°c



3759323

GRUPPO DOCCIA SHRINK KL H.60 GRIGIO

comando leva lunga 220 mm
canna ø 25 x 175 mm
doccia BEST versione PRO
attacchi ø 3/8" F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata 60°c

SHOWER GROUP SHRINK KL H.60 GREY

long lever control 220 mm
spout ø 25x175 mm
shower BEST version PRO
fittings ø 3/8" F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK KL H.60 GRAU

lange Hebelbedienung 220 mm
Rohr ø 25 x 175 mm
Dusche BEST Mod. PRO
Anschlüsse ø 3/8" F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60°c

GRUPO DUCHA SHRINK KL H.60 GRIS

mando con palanca larga 220 mm
caño ø 25 x 175 mm
ducha BEST versión PRO
conexiones ø 3/8" F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max 10 bar
temperatura max 90°c aconsejada 60°c





3759324

GRUPPO DOCCIA SHRINK KL H.70 GRIGIO

comando leva lunga 220 mm
canna ø 25 x 175 mm
doccia BEST versione PRO
attacchi ø 3/8F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata 60°c

SHOWER GROUP SHRINK KL H.70 GREY

long lever control 220 mm
spout ø 25x175 mm
shower BEST version PRO
fittings ø 3/8F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK KL H.70 GRAU

lange Hebelbedienung 220 mm
Rohr ø 25 x 175 mm
Dusche BEST Mod. PRO
Anschlüsse ø 3/8" F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60°c

GRUPO DUCHA SHRINK KL H.70 GRIS

mando con palanca larga 220 mm
caño ø 25 x 175 mm
ducha BEST versión PRO
conexiones ø 3/8" F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max 10 bar
temperatura max 90°c aconsejada 60°c

3759325

GRUPPO DOCCIA SHRINK KL H.70 NERO

comando leva lunga 220 mm
canna ø 25 x 175 mm
doccia BEST versione PRO
attacchi ø 3/8F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata 60°c

SHOWER GROUP SHRINK KL H.70 BLACK

long lever control 220 mm
spout ø 25x175 mm
shower BEST version PRO
fittings ø 3/8F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK KL H.70 SCHWARZ

lange Hebelbedienung 220 mm
Rohr ø 25 x 175 mm
Dusche BEST Mod. PRO
Anschlüsse ø 3/8" F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60°c

GRUPO DUCHA SHRINK KL H.70 NEGRO

mando palanca larga 220 mm
caño ø 25 x 175 mm
ducha BEST versión PRO
conexiones ø 3/8F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max 10 bar
temperatura max 90°C aconsejada 60°C



3759326

GRUPPO DOCCIA SHRINK H.80 NERO

comando leva lunga 220 mm
canna ø 25 x225 mm
doccia BEST versione PRO
attacchi ø 3/8F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata 60°c

SHOWER GROUP SHRINK H.80 BLACK

long lever control 220 mm
spout ø 25x225 mm
shower BEST version PRO
fittings ø 3/8F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK H.80 SCHWARZ

lange Hebelbedienung 220 mm
Rohr ø 25 x 225 mm
Dusche BEST Mod. PRO
Anschlüsse ø 3/8" F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60°c

GRUPO DUCHA SHRINK H.80 NEGRO

mando palanca larga 220 mm
caño ø 25 x 225 mm
ducha BEST versión PRO
conexiones ø 3/8F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max 10 bar
temperatura max 90°C aconsejada 60°C



3759327

GRUPPO DOCCIA SHRINK KL H.80 GRIGIO

comando leva lunga 220 mm
canna ø 25 x 225 mm
doccia BEST versione PRO
attacchi ø 3/8F
con valvole antiriflusso
dima foratura ø 30 mm
pressione nax 10 bar
temperatura max 90°c consigliata 60°c

SHOWER GROUP SHRINK KL H.80 GREY

long lever control 220 mm
tube ø 25 x 225 mm
shower BEST version PRO
fittings ø 3/8F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK KL H.80 GRAU

lange Hebelbedienung 220 mm
Rohr ø 25 x 225 mm
Dusche BEST Mod. PRO
Anschlüsse ø 3/8" F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60°c

GRUPO DUCHA SHRINK H.80 GRIS

mando palanca larga 220 mm
caño ø 25 x 225 mm
ducha BEST versión PRO
conexiones ø 3/8F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max 10 bar
temperatura max 90°C aconsejada 60°C





3759328

GRUPPO DOCCIA SHRINK PISA H.60 BIANCO

comando leva corta
doccia BEST versione HOME
attacchi ø 3/8F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata 60°c

SHOWER GROUP SHRINK PISA H.60 WHITE

short lever control
shower BEST version HOME
fittings ø 3/8F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK PISA H.60 WEISS

kurze Hebelbedienung
Dusche BEST Mod. HOME
Anschlüsse ø 3/8" F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60°c

GRUPO DUCHA SHRINK PISA H.60 BLANCO

mando palanca corta
ducha BEST versión HOME
conexiones ø 3/8F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max 10 bar
temperatura max 90°C aconsejada 60°C

3759329

GRUPPO DOCCIA SHRINK PISA H.70 NERO

comando leva corta
doccia BEST versione SEMI
attacchi ø 3/8F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata 60°c

SHOWER GROUP SHRINK PISA H.70 BLACK

short lever control
shower BEST version SEMI
fittings ø 3/8F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK PISA H.70 SCHWARZ

kurze Hebelbedienung
Dusche BEST Mod. SEMI
Anschlüsse ø 3/8" F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60°c

GRUPO DUCHA SHRINK PISA H.70 NEGRO

mando palanca corta
ducha BEST versión SEMI
conexiones ø 3/8F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max 10 bar
temperatura max 90°C aconsejada 60°C



3759330

GRUPPO DOCCIA SHRINK PISA H.80 GRIGIO

comando leva corta
doccia BEST versione PRO
attacchi ø 3/8F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata 60°c

SHOWER GROUP SHRINK PISA H.80 GREY

short lever control
shower BEST version PRO
fittings ø 3/8F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK PISA H.80 GRAU

kurze Hebelbedienung
Dusche BEST Mod. PRO
Anschlüsse ø 3/8" F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60°c

GRUPO DUCHA SHRINK PISA H.80 GRIS

mando palanca corta
ducha BEST versión PRO
conexiones ø 3/8F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max 10 bar
temperatura max 90°C aconsejada 60°C





3759331

GRUPPO DOCCIA SHRINK STYL H.60 BIANCO

comando a leva 1/4" di giro
doccia BEST versione HOME
attacchi ø 3/8F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata 60°c

SHOWER GROUP SHRINK STYL H.60 WHITE

lever control 1/4" turn
shower BEST version HOME
fittings ø 3/8F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK STYL H.60 WEISS

Hebelbedienung 1/4" Umdrehung
Dusche BEST Mod. HOME
Anschlüsse ø 3/8" F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60°c

GRUPO DUCHA SHRINK STYL H.60 BLANCO

mando palanca 1/4" revolución
ducha BEST versión HOME
conexiones ø 3/8F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max 10 bar
temperatura max 90°C aconsejada 60°C

3759332

GRUPPO DOCCIA SHRINK STYL H.60 NERO

comando a leva 1/4" di giro
doccia BEST versione PRO
attacchi ø 3/8F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata 60°c

SHOWER GROUP SHRINK STYL H.60 BLACK

lever control 1/4" turn
shower BEST version PRO
fittings ø 3/8F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK STYL H.60 SCHWARZ

Hebelbedienung 1/4" Umdrehung
Dusche BEST Mod. PRO
Anschlüsse ø 3/8" F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60°c

GRUPO DUCHA SHRINK STYL H.60 NEGRO

mando palanca 1/4" revolución
ducha BEST versión PRO
conexiones ø 3/8F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max 10 bar
temperatura max 90°C aconsejada 60°C





3759333

GRUPPO DOCCIA SHRINK STYL H.70 GRIGIO

comando a leva 1/4" di giro
doccia BEST versione SEMI
attacchi ø 3/8F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata 60°c

SHOWER GROUP SHRINK STYL H.70 GREY

lever control 1/4" turn
shower BEST version SEMI
fittings ø 3/8F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK STYL H.70 GRAU

Hebelbedienung 1/4" Umdrehung
Dusche BEST Mod. SEMI
Anschlüsse ø 3/8" F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60°c

GRUPO DUCHA SHRINK STYL H.70 GRIS

mando palanca 1/4" revolución
ducha BEST versión SEMI
conexiones ø 3/8F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max 10 bar
temperatura max 90°C aconsejada 60°C

3759334

GRUPPO DOCCIA SHRINK STYL H.80 NERO

comando a leva 1/4" di giro
doccia BEST versione PRO
attacchi ø 3/8F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata 60°c

SHOWER GROUP SHRINK STYL H.80 BLACK

lever control 1/4" turn
shower BEST version PRO
fittings ø 3/8F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK STYL H.80 SCHWARZ

Hebelbedienung 1/4" Umdrehung
Dusche BEST Mod. PRO
Anschlüsse ø 3/8" F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60°c

GRUPO DUCHA SHRINK STYL H.80 NEGRO

mando palanca 1/4" revolución
ducha BEST versión PRO
conexiones ø 3/8F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max 10 bar
temperatura max 90°C aconsejada 60°C





3759354

GRUPPO DOCCIA SHRINK HEAVY-D H.70 BIANCO

canna ø 20 x190 mmm
doccia BEST versione SEMI
attacchi ø 3/8F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata
60° C

SHOWER GROUP SHRINK HEAVY-D H.70 WHITE

spout ø 20x190 mm
shower BEST version SEMI
fittings ø 3/8"F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended
60°c

DUSCHGRUPPE SHRINK HEAVY-D H.70 WEISS

Rohr ø 20 x190 mmm
Dusche BEST Mod. SEMI
Anschlüsse ø 3/8F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen
60° C

GRUPO DUCHA SHRINK HEAVY-D H.70 BLANCO

caño ø 20 x190 mmm
ducha BEST mod. SEMI
conexiónes ø 3/8F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max max 10 bar
temperatura max 90°c aconsejada
60° C

3759355

GRUPPO DOCCIA SHRINK HEAVY-D H.70 NERO

canna ø 20 x190 mmm
doccia BEST versione SEMI
attacchi ø 3/8F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata
60° C

SHOWER GROUP SHRINK HEAVY-D H.70 BLACK

spout ø 20x190 mm
shower BEST version SEMI
fittings ø 3/8"F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended
60°c

DUSCHGRUPPE SHRINK HEAVY-D H.70 SCHWARZ

Rohr ø 20 x190 mmm
Dusche BEST Mod. SEMI
Anschlüsse ø 3/8F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen
60° C

GRUPO DUCHA SHRINK HEAVY-D H.70 NEGRO

caño ø 20 x190 mmm
ducha BEST mod. SEMI
conexiónes ø 3/8F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max max 10 bar
temperatura max 90°c aconsejada
60° C





3759356

GRUPPO DOCCIA SHRINK HEAVY-D H.80 GRIGIO

canna ø 20 x190 mm
doccia BEST versione PRO
attacchi ø 3/8"F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata 60° C

SHOWER GROUP SHRINK HEAVY-D H.80 GRAY

spout ø 20x190 mm
shower BEST version PRO
fittings ø 3/8"F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK HEAVY-D H.80 GRAU

Rohr ø 20 x190 mmm
Dusche BEST Mod. PRO
Anschlüsse ø 3/8F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60° C

GRUPO DUCHA SHRINK HEAVY-D H.80 GRIS

caño ø 20 x190 mmm
ducha BEST mod. PRO
conexiónes ø 3/8F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max max 10 bar
temperatura max 90°c aconsejada 60° C

3759357

GRUPPO DOCCIA SHRINK HEAVY-D H.80 NERO

canna ø 20 x190 mm
doccia BEST versione PRO
attacchi ø 3/8"F
con valvole antiriflusso
dima foratura ø 30 mm
pressione max 10 bar
temperatura max 90°c consigliata 60° C

SHOWER GROUP SHRINK HEAVY-D H.80 BLACK

spout ø 20x190 mm
shower BEST version PRO
fittings ø 3/8"F
with non-return valves
mounting hole ø 30 mm
pressure max 10 bar
temperature max 90°c recommended 60°c

DUSCHGRUPPE SHRINK HEAVY-D H.80 SCHWARZ

Rohr ø 20 x190 mmm
Dusche BEST Mod. PRO
Anschlüsse ø 3/8F
mit Rückschlagventilen
Einbaumass ø 30 mm
Druck max 10 bar
Temperatur max 90°c empfohlen 60° C

GRUPO DUCHA SHRINK HEAVY-D H.80 NEGRO

caño ø 20 x190 mmm
ducha BEST mod. PRO
conexiónes ø 3/8F
con válvulas anti-reflujo
plantilla de perforación ø 30 mm
presión max max 10 bar
temperatura max 90°c aconsejada 60° C

COLORI DIVERSI SU RICHIESTA
DIFFERENT COLOURS ON DEMAND
VERSCHIEDENE FARBEN AUF ANFRAGE
DIFERENTES COLORES A PETICIÓN







DOCCIA BEST - Versione HOME
SHOWER BEST - Mod. HOME
DUSCHE BEST - Mod. HOME
DUCHA BEST - Mod. HOME



Leva in plastica colorata
Coloured plastic lever
Hebel aus gefärbtem Kunststoff
Palanca de plástico colorado

DOCCIA BEST - Versione SEMI
SHOWER BEST - Mod. SEMI
DUSCHE BEST - Mod. SEMI
DUCHA BEST - Mod. SEMI



Leva in ottone cromato
Chrome plated brass lever
Hebel aus verchromtem Messing
Palanca de latón cromado

DOCCIA BEST - Versione PRO
SHOWER BEST - Mod. PRO
DUSCHE BEST - Mod. PRO
DUCHA BEST - Mod. PRO



Leva in ottone cromato e anello per l'erogazione continua
Chrome plated brass lever and ring for the continuous flow
Hebel aus verchromtem Messing und Ring zum Dauerauslauf
Palanca de latón cromado y aro para la erogación continua

The most advanced one-stop shop portal for **spare parts** & **accessories**







56,000
items always in stock
292,000
cross references to manufacturers' codes
2,300,000
items in our database, available upon request

The most complete and powerful online ordering service

Always with you… anywhere, anytime,
7 days / 24 hours

www.lfspareparts724.com

rubinetterie del friuli

p. 15 Rubinetti e miscelatori per doccia
Taps and mixers for showers
Wasserarmaturen und Mischbatterien für Wasserhähne
Grifos y mezcladores para ducha

p. 16 Docce prelavaggio
Pre-rinse units
Waschbrausen & Zubehör
Duchas pre-lavado

p. 25 Miscelatori a leva
Lever mixers
Hebelmischer
Mezcladores de palanca

p. 28 Rubinetti e miscelatori per lavelli
Taps and mixers for sinks
Wasserarmaturen und Mischbatterien für Waschbecken
Grifos y mezcladores para lavabos



3759316

MISCELATORE BIFORO DA BANCO

per attacco doccia
interasse 155 mm
attacchi ø 3/4"
dima di foratura ø 27 mm

TWO-HOLE BENCH MIXER

for shower unit fitting
distance 155 mm
fitting ø 3/4"
mounting hole ø 27 mm

ZWEILÖCHER-TISCHMISCHBATTERIE

für Dusche-Anschluss
Achsabstand 155 mm
Anschlüsse ø 3/4"
Einbaumass ø 27 mm

MEZCLADOR 2 AGUJEROS PARA BANCO

para conexión ducha
distancia entre ejes 155 mm
conexiones 3/4"
plantilla de perforación 27 mm



3759315

MISCELATORE BIFORO DA BANCO

per attacco doccia
interasse 155 mm
attacchi ø 1/2"
dima di foratura ø 22 mm

TWO-HOLE BENCH MIXER

for shower unit fitting
distance 155 mm
fitting ø 1/2"
mounting hole ø 22 mm

ZWEILÖCHER-TISCHMISCHBATTERIE

für Dusche-Anschluss
Achsabstand 155 mm
Anschlüsse ø 1/2"
Einbaumass ø 22 mm

MEZCLADOR 2 AGUJEROS PARA BANCO

para conexión ducha
distancia entre ejes 155 mm
conexiones ø 1/2"
plantilla de perforación ø 22 mm



3759314

MISCELATORE MONOFORO A LEVA

per attacco doccia
attacchi 1/2"M
dima di foratura 32 mm

SINGLE-HOLE LEVER OPERATED MIXER

for shower connection
fitting ø 1/2"M
mounting hole 32 mm

EINLOCH-MISCHBATTERIE MIT HEBEL

für Dusche-Anschluss
Anschlüsse 1/2"M
Einbaumass min 30 max 32 mm

MEZCLADOR 1 AGUJERO C/PALANCA

para conexión ducha
conexiones 1/2"M
plantilla de perforación 32 mm



3759313

MISCELATORE MONOFORO A LEVA

per attacco doccia
attacchi 1/2"M
dima di foratura 32mm

SINGLE-HOLE LEVER OPERATED MIXER

for shower connection
fitting ø 1/2"M
mounting hole 32 mm

EINLOCH-MISCHBATTERIE MIT HEBEL

für Dusche-Anschluss
Anschlüsse 1/2"M
Einbaumass min 30 max 32 mm

MEZCLADOR 1 AGUJERO C/PALANCA

para conexión ducha
conexiones 1/2"M
plantilla de perforación 32 mm



3759312

MISCELATORE MONOFORO ECO 1/4" DI GIRO

per attacco doccia
attacchi 1/2"M
dima di foratura minimo 30 massimo 32 mm

ONE HOLE MIXER ECO 1/4" TURN

for shower connection
fitting ø 1/2"M
mounting hole min 30 max 32 mm


EINLOCH-MISCHBATTERIE ECO 1/4" UMDREHUNG

für Dusche-Anschluss
Anschlüsse 1/2"M
Einbaumass min 30 max 32 mm

MEZCLADOR 1 AGUJERO ECO 1/4" DE VUELTA

para conexión ducha
conexiones 1/2"M
plantilla de perforación min. 30 max. 32 mm





3759339

GRUPPO DOCCIA TOP-CLASS 1/4" DI GIRO

con set di prelavaggio
attacchi ø 1/2 F x 400 mm
portata 17 l/min a 3 bar
dima di foratura 30 mm

SHOWER GROUP TOP-CLASS 1/4" TURN

with prewash set
fittings ø 1/2 F x 400 mm
flow rate 17 l/min a 3 bar
mounting hole 30 mm


DUSCHGRUPPE TOP-CLASS 1/4" UMDREHUNG

mit Pendelbrause
Anschlüsse ø 1/2 F x 400 mm
Fördermenge 17 l/min 3 bar
Einbaumass 30 mm

GRUPO DUCHA TOP-CLASS 1/4" DE REVOL.GIRO

con juego de prelavado
conexiones ø 1/2 F x 400 mm
caudal 17 L/min a 3 bar
plantilla de perforación 30 mm





3759344

GRUPPO DOCCIA TOP-CLASS CON CANNA

con set di prelavaggio
comandi a leva 1/4" di giro
canna a metà tubo ø 18 x 250 mm
attacchi ø 1/2 F x 400 mm
portata 20 l/min a 3 bar
dima di foratura 30 mm

SHOWER GROUP TOP-CLASS WITH SPOUT


with prewash set
lever control 1/4" turn
half tube spout ø 18 x 250 mm
fittings ø 1/2 F x 400 mm
flow rate 20 l/min a 3 bar
mounting hole 30 mm

DUSCHGRUPPE TOP-CLASS MIT ROHR

mit Pendelbrause
Hebelbedienung 1/4" Umdrehung
Auslauf bei Rohrhälfte ø 18x250 mm
Anschlüsse ø 1/2 F x 400 mm
Fördermenge 20 l/min 3 bar
Einbaumass 30 mm

GRUPO DUCHA TOP-CLASS CON CAÑO

con juego de prelavado
mandos de palanca 1/4" de revolución
caño a medio del tubo ø 18 x 250 mm
conexiones ø 1/2 F x 400 mm
caudal 20 L/min a 3 bar
plantilla de perforación 30 mm



7103516

MISCELATORE BIFORO

miscelatore 2 fori acqua calda/fredda
comandi 1/4 di giro
canna ø 18x250 mm
portata 20 L/min 4 bar
attacchi ø 1/2"MM
interasse 160 mm
dima di foratura ø 22 mm
lunghezza flessibile 1100 mm
pressione max 5 bar
pressione min per un buon funzionamento 2,5 bar

TWO-HOLE MIXER

two hole mixer hot/cold water
fitting ø 1/2" MM
hole distance 160 mm
1/4 turn commands
regulation 24 L/min. 4 bar
tube ø 18x250 mm
flexible length 1100 mm
hole distance ø from 22 to 27 mm
pressure max 5 bar
pressure min for a proper functioning 2,5 bar

ZWEILÖCHER-MISCHBATTERIE

Mischbatterie 2 Löcher Wasser warm/kalt
Anschluss ø 1/2" MM
Achsabstand 160 mm
Schaltungen 1/4 Umdrehung
Regulierung 24 L/min. 4 bar
Rohr ø 18x250 mm
flexible Länge 1100 mm
Einbaumass ø 22 à 27 mm
Druck max 5 bar
Druck min für einen guten Betrieb 2,5 bar

MEZCLADOR 2 AGUJEROS

mezclador 2 agujeros agua caliente/fría
racor ø 1/2" MM
distancia entre ejes 160 mm
mandos 1/4 de vuelta
regulación 24 L/min. 4 bar
caño ø 18x250 mm
longitud flexible 1100 mm
plantilla de perforación ø 22 a 27 mm
presión max 5 bar
presión min para un buen funcionamiento 2,5 bar



3759342

GRUPPO DOCCIA TOP-CLASS BIFORO

con set di prelavaggio
comandi a leva 1/4" di giro
interasse fori 155 mm
attacchi ø 1/2 F x 400 mm
portata 20 l/min a 3 bar
dima di foratura 22 mm

DOUBLE HOLE SHOWER GROUP TOP-CLASS

with prewash set
lever control 1/4" turn
distance between holes 155 mm
fittings ø 1/2 F x 400 mm
flow rate 20 l/min a 3 bar
mounting hole 22 mm

DUSCHGRUPPE TOP-CLASS 2-LÖCHER

mit Pendelbrause
Hebelbedienung 1/4" Umdrehung
Löcherachsabstand 155 mm
Anschlüsse ø 1/2 F x 400 mm
Fördermenge 20 l/min 3 bar
Einbaumass 22 mm

GRUPO DUCHA TOP-CLASS 2 AGUJEROS

con juego de prelavado
mandos de palanca 1/4" de revolución
distancia entre ejes 155 mm
conexiones ø 1/2 F x 400 mm
caudal 20 L/min a 3 bar
plantilla de perforación 22 mm



3759340

GRUPPO DOCCIA TOP-CLASS A LEVA EDEN

con set di prelavaggio
attacchi ø 1/2 F x 400 mm
portata 17 l/min a 3 bar
dima di foratura 30 mm

SHOWER GROUP TOP-CLASS WITH EDEN LEVER

with prewash set
fittings ø 1/2 F x 400 mm
flow rate 17 l/min a 3 bar
mounting hole 30 mm

DUSCHGRUPPE TOP-CLASS M/HEBEL EDEN

mit Pendelbrause
Anschlüsse ø 1/2 F x 400 mm
Fördermenge 17 l/min 3 bar
Einbaumass 30 mm

GRUPO DUCHA TOP-CLASS PALANCA EDEN

con juego de prelavado
conexiones ø 1/2 F x 400 mm
caudal 17 L/min a 3 bar
plantilla de perforación 30 mm



3759341

GRUPPO DOCCIA TOP-CLASS A LEVA CLINICA

con set di prelavaggio
attacchi ø 1/2 F x 400 mm
portata 17 l/min a 3 bar
dima di foratura 30 mm

SHOWER GROUP TOP-CLASS CLINIC LEVER

with prewash set
fittings ø 1/2 F x 400 mm
flow rate 17 l/min a 3 bar
mounting hole 30 mm

DUSCHGRUPPE TOP-CLASS M/KLIN. HEBEL

mit Pendelbrause
Anschlüsse ø 1/2 F x 400 mm
Fördermenge 17 l/min 3 bar
Einbaumass 30 mm

GRUPO DUCHA TOP-CLASS PALANCA CLÍNICA

con juego de prelavado
conexiones ø 1/2 F x 400 mm
caudal 17 L/min a 3 bar
plantilla de perforación 30 mm



3759346

GRUPPO DOCCIA SKY LEVA CLINICA

con set di prelavaggio
attacchi ø 1/2 F x 400 mm
portata 18 l/min a 3 bar
dima di foratura 30/32 mm

SHOWER GROUP SKY LEVER CLINIC

with prewash set
fittings ø 1/2 F x 400 mm
flow rate 18 l/min a 3 bar
mounting hole 30/32 mm

DUSCHGRUPPE SKY M/ KLINISCHEM HEBEL

mit Pendelbrause
Anschlüsse ø 1/2 F x 400 mm
Fördermenge 18 l/min 3 bar
Einbaumass 30/32 mm

GRUPO DUCHA SKY PALANCA CLÍNICA

con juego de prelavado
conexiones ø 1/2 F x 400 mm
caudal 18 L/min a 3 bar
plantilla de perforación 30/32 mm



3759337

GRUPPO DOCCIA TOP-CLASS OMEGA

con set di prelavaggio
attacchi ø 1/2 F x 400 mm
portata 17 l/min a 3 bar
dima di foratura 30 mm

SHOWER GROUP TOP-CLASS OMEGA

with prewash set
fittings ø 1/2 F x 400 mm
flow rate 17 l/min a 3 bar
mounting hole 30 mm

DUSCHGRUPPE TOP-CLASS OMEGA

mit Pendelbrause
Anschlüsse ø 1/2 F x 400 mm
Fördermenge 17 l/min 3 bar
Einbaumass 30 mm

GRUPO DUCHA TOP-CLASS OMEGA

con juego de prelavado
conexiones ø 1/2 F x 400 mm
caudal 17 L/min a 3 bar
plantilla de perforación 30 mm



3759343

GRUPPO DOCCIA TOP-CLASS CON CANNA

con set di prelavaggio
canna a metà tubo ø 18 x 250 mm
attacchi ø 1/2 F x 400 mm
portata 17/min a 3 bar
dima di foratura 30 mm

SHOWER GROUP TOP-CLASS WITH SPOUT

with prewash set
half tube spout ø 18 x 250 mm
fittings ø 1/2 F x 400 mm
flow rate 17 l/min a 3 bar
mounting hole 30 mm

DUSCHGRUPPE TOP-CLASS MIT ROHR

mit Pendelbrause
Auslauf bei Rohrhälfte ø 18x250 mm
Anschlüsse ø 1/2 F x 400 mm
Fördermenge 17 l/min 3 bar
Einbaumass 30 mm

GRUPO DUCHA TOP-CLASS CON CAÑO

con juego de prelavado
caño a medio del tubo ø 18 x 250 mm
conexiones ø 1/2 F x 400 mm
caudal 17 L/min a 3 bar
plantilla de perforación 30 mm



3759347

GRUPPO DOCCIA SKY BIFORO

con set di prelavaggio
attacchi ø 1/2 F
interasse 155 mm x 400 mm
portata 17 l/min a 3 bar
dima di foratura 22 mm

TWO-HOLE SHOWER GROUP SKY

with prewash set
fittings ø 1/2 F
distance between holes 155 mm x 400 mm
flow rate 17 l/min a 3 bar
mounting hole 22 mm

DUSCHGRUPPE SKY 2-LÖCHER

mit Pendelbrause
Anschlüsse ø 1/2F
Achsabstand 155 mm x 400 mm
Fördermenge 17 l/min 3 bar
Einbaumass 22 mm

GRUPO DUCHA SKY 2 AGUJEROS

con juego de prelavado
conexiones ø 1/2 F
distancia entre ejes 155 mm x 400 mm
caudal 17 L/min a 3 bar
plantilla de perforación 22 mm



3759348

GRUPPO DOCCIA SKY BIFORO CON CANNA

con set di prelavaggio
canna a metà tubo ø 18 x 250 mm
attacchi ø 1/2
interasse 155 mm
portata 17 l/min a 3 bar
dima di foratura 22 mm

TWO-HOLE SHOWER GROUP SKY WITH SPOUT

with prewash set
half tube spout ø 18 x 250 mm
fittings ø 1/2
distance between holes 155 mm
flow rate 17 l/min a 3 bar
mounting hole 22 mm

DUSCHGRUPPE SKY 2-LÖCHER MIT ROHR

mit Pendelbrause
Auslauf bei Rohrhälfte ø 18x250 mm
Anschlüsse ø 1/2
Achsabstand 155 mm
Fördermenge 17 l/min 3 bar
Einbaumass 22 mm

GRUPO DUCHA SKY 2 AGUJEROS CON CAÑO

con juego de prelavado
caño a medio del tubo ø 18 x 250 mm
conexiones ø 1/2
distancia entre ejes 155 mm
caudal 17 L/min a 3 bar
plantilla de perforación 22 mm



3759345

GRUPPO DOCCIA TOP-CLASS BIFORO CON CANNA

con set di prelavaggio
canna a metà tubo ø 18 x250 mm
interasse fori 155 mm
attacchi ø 1/2 F x 400 mm
portata 20 l/min a 3 bar
dima di foratura 22 mm

DOUBLE HOLE SHOWER GROUP TOP-CLASS SPOUT

with prewash set
half tube spout ø 18 x 250 mm
distance between holes 155 mm
fittings ø 1/2 F x 400 mm
flow rate 20 l/min a 3 bar
mounting hole 22 mm


DUSCHGRUPPE TOP-CLASS 2-LÖCHER M/ROHR

mit Pendelbrause
Auslauf bei Rohrhälfte ø 18x250 mm
Löcherachsabstand 155 mm
Anschlüsse ø 1/2 F x 400 mm
Fördermenge 20 l/min 3 bar
Einbaumass 22 mm


GRUPO DUCHA TOP-CLASS 2AGUJEROS CON CAÑO

con juego de prelavado
caño a medio del tubo ø 18 x 250 mm
distancia entre ejes 155 mm
conexiones ø 1/2 F x 400 mm
caudal 20 L/min a 3 bar
plantilla de perforación 22 mm









3759349

GRUPPO DOCCIA MIGNON H 650

con set di prelavaggio
manopole OMEGA
attacchi ø 1/2 F x 400 mm
portata 17 l/min a 3 bar
dima di foratura 30/32 mm

SHOWER GROUP MIGNON H 650

with prewash set
knob OMEGA
fittings ø 1/2 F x 400 mm
flow rate 17 l/min a 3 bar
mounting hole 30/32 mm

DUSCHGRUPPE MIGNON H 650

mit Pendelbrause
Drehknöpfe OMEGA
Anschlüsse ø 1/2 F x 400 mm
Fördermenge 17 l/min 3 bar
Einbaumass 30/32 mm

GRUPO DUCHA MIGNON H 650

con juego de prelavado
mandos OMEGA
conexiones ø 1/2 F x 400 mm
caudal 17 L/min a 3 bar
plantilla de perforación 30/32 mm

3759350

GRUPPO DOCCIA MIGNON H 650 1/4"DI GIRO

con set di prelavaggio
comando a leva 1/4"di giro
attacchi ø 1/2 F x 400 mm
portata 17 l/min a 3 bar
dima di foratura 30/32 mm

SHOWER GROUP MIGNON H 650 1/4"TURN

with prewash set
lever control 1/4" turn
fittings ø 1/2 F x 400 mm
flow rate 17 l/min a 3 bar
mounting hole 30/32 mm


DUSCHGRUPPE MIGNON H 650 1/4"UMDREHUNG

mit Pendelbrause
Hebelbedienung 1/4" Umdrehung
Anschlüsse ø 1/2 F x 400 mm
Fördermenge 17 l/min 3 bar
Einbaumass 30/32 mm

GRUPO DUCHA MIGNON H 650 1/4" REVOL.

con juego de prelavado
mando de palanca 1/4" de revolución
conexiones ø 1/2F x 400 mm
caudal 17 L/min a 3 bar
plantilla de perforación 30/32 mm





3759351

GRUPPO DOCCIA MIGNON H 650 LEVA CLINICA

con set di prelavaggio
leva clinica 220 mm
canna fusa 200 mm
attacchi ø 1/2 F x 400 mm
portata 17 l/min a 3 bar
dima di foratura 32/34 mm

SHOWER GROUP MIGNON H 650 CLINIC LEVER

with prewash set
lever clinic 220 mm
melted spout 200 mm
fittings ø 1/2 F x 400 mm
flow rate 17 l/min a 3 bar
mounting hole 32/34 mm

DUSCHGRUPPE MIGNON H 650 M/KLIN. HEBEL

mit Pendelbrause
mit klinischem Hebel 220 mm
Gussauslauf 200 mm
Anschlüsse ø 1/2 F x 400 mm
Fördermenge 17 l/min 3 bar
Einbaumass 32/34 mm

GRUPO DUCHA MIGNON H 650 PALANCA CLÍNICA

con juego de prelavado
palanca clínica 220 mm
caño fundido 200 mm
conexiones ø 1/2F x 400 mm
caudal 17 L/min a 3 bar
plantilla de perforación 32/34 mm



3759353

GRUPPO DOCCIA MATIC CON CANNA

con set di prelavaggio
canna a metà tubo ø 18 x 200 mm
attacchi ø 1/2 F x 400 mm
portata 15 l/min a 3 bar
dima di foratura 30/32 mm

SHOWER GROUP MATIC WITH LEVER

with prewash set
half tube spout ø 18 x 200 mm
fittings ø 1/2 F x 400 mm
flow rate 15 l/min a 3 bar
mounting hole 30/32 mm

DUSCHGRUPPE MATIC MIT ROHR

mit Pendelbrause
Auslauf bei Rohrhälfte ø 18x200 mm
Anschlüsse ø 1/2 F x 400 mm
Fördermenge 15 l/min 3 bar
Einbaumass 30/32 mm

GRUPO DUCHA MATIC CON CAÑO

con juego de prelavado
caño a medio del tubo ø 18 x 200 mm
conexiones ø 1/2 F x 400 mm
caudal 15 L/min a 3 bar
plantilla de perforación 30/32 mm



3759352

GRUPPO DOCCIA MATIC

con set di prelavaggio
attacchi ø 1/2 F x 400 mm
portata 15 l/min a 3 bar
dima di foratura 30/32 mm

SHOWER GROUP MATIC

with prewash set
fittings ø 1/2 F x 400 mm
flow rate 15 l/min a 3 bar
mounting hole 30/32 mm


DUSCHGRUPPE MATIC

mit Pendelbrause
Anschlüsse ø 1/2 F x 400 mm
Fördermenge 15 l/min 3 bar
Einbaumass 30/32 mm

GRUPO DUCHA MATIC

con juego de prelavado
conexiones ø 1/2F x 400 mm
caudal 15 L/min a 3 bar
plantilla de perforación 30/32 mm





3259031

MISCELATORE MONOCOMANDO A LEVA

canna ø 22x200 mm
attacco ø 1/2"F
portata 18 L/min a 3 bar
dima di foratura 30 mm

SINGLE-HOLE LEVER MIXER

spout ø 22x200 mm
fitting ø 1/2"F
capacity 18 L/min 3 bar
mounting hole ø 30 mm


EINHEBEL-MISCHBATTERIE

Auslauf ø 22x200 mm
Anschluss ø 1/2"F
Fördermenge 18 L/Min 3 bar
Einbaumass ø 30 mm

MEZCLADOR MONOMANDO CON PALANCA

caño ø 22x200 mm
conexiones ø 1/2"F
caudal 18 L/min a 3 bar
plantilla de perforación ø 30 mm





3259033

MISCELATORE MONOFORO A LEVA CLINICA

canna erogazione fusa 300 mm
attacchi ø 3/8"Fx400 mm
portata 15 L/min a 3 bar
pressione max 5 bar
dima di foratura ø 35 mm

SINGLE-HOLE MIXER WITH CLINIC LEVER

melted spout 300 mm
connections ø 3/8"Fx400 mm
flow rate 15 L/min a 3 bar
max pressure 5 bar
mounting hole ø 35 mm

EINLOCH-MISCHBATTERIE MIT KLINIKHEBEL

Auslaufrohr 300 mm
Anschlüsse ø 3/8"Fx400 mm
Wasserdurchfluss 15 L/min mit 3 bar
max. Druck 5 bar
Einbaumass ø 35 mm

MEZCLADOR 1 AGUJERO CON PALANCA CLINICA

caño erogación fundido 300 mm
conexiones ø 3/8"Fx400 mm
caudal 15 L/min a 3 bar
presión max 5 bar
plantilla de perforación ø 35 mm





3259032

MISCELATORE MONOFORO A LEVA EDEN

canna erogazione fusa 300 mm
attacchi ø 3/8"Fx400 mm
portata 15 L/min a 3 bar
pressione max 5 bar
dima di foratura ø 35 mm

SINGLE-HOLE MIXER WITH EDEN LEVER

melted spout 300 mm
connections ø 3/8"Fx400 mm
flow rate 15 L/min a 3 bar
max pressure 5 bar
mounting hole ø 35 mm


EINLOCH-MISCHBATTERIE MIT HEBEL EDEN

Auslaufrohr 300 mm
Anschlüsse ø 3/8"Fx400 mm
Wasserdurchfluss 15 L/min mit 3 bar
max. Druck 5 bar
Einbaumass ø 35 mm

MEZCLADOR 1 AGUJERO CON PALANCA EDEN

caño erogación fundido 300 mm
conexiones ø 3/8"Fx400 mm
caudal 15 L/min a 3 bar
presión max 5 bar
plantilla de perforación ø 35 mm





3259034

MISCELATORE MONOFORO C40 LEVA CLINICA

canna erogazione fusa 250 mm
attacchi ø 1/2"Fx400 mm
portata 18 L/min a 3 bar
pressione max 5 bar
dima di foratura ø 32 mm

SINGLE-HOLE MIXER C40 CLINIC LEVER

melted spout 250 mm
connections ø 1/2"Fx400 mm
flow rate 18 L/min a 3 bar
max pressure 5 bar
mounting hole ø 32 mm

EINLOCH-MISCHBATTERIE C40 KLINIKHEBEL

Auslaufrohr 250 mm
Anschlüsse ø 1/2"Fx400 mm
Wasserdurchfluss 18 L/min mit 3 bar
max. Druck 5 bar
Einbaumass 32 mm

MEZCLADOR 1 AGUJERO C40 PALANCA CLINICA

caño erogación fundido 250 mm
conexiones ø 1/2"Fx400 mm
caudal 18 L/min a 3 bar
presión max 5 bar
plantilla de perforación ø 32 mm



3259035

MISCELATORE MONOFORO DOCCIA ESTRAIBILE

leva corta tipo EDEN
attacchi ø 3/8"Fx400 mm
portata 13 L/min a 3 bar
pressione max 5 bar
dima di foratura ø 40 mm

SINGLE-HOLE MIXER EXTRACTABLE SHOWER

short lever EDEN
flow rate 13 l/min.a 3 bar
fittings 3/8"F X 400 mm
max pressure 5 bar
mounting hole 40 mm

EINLOCH-MISCHBATTERIE DUSCHE HERAUSZIEH.

Hebel klein EDEN
Wasserdurchfluss 13 L/Min. mit 3 Bar
Anschlüsse 3/8"F x 400 mm
Max Druck 5 Bar
Einbaumass 40 mm

MEZCLADOR 1 AGUJERO DUCHA EXTRAIBLE

palanca corta EDEN
caudal 13 l/min.a 3 bar
conexiones 3/8"F X 400 mm
presión max 5 bar
plantilla de perforación 40 mm



3259036

MISCELATORE MONOFORO DOCCIA ESTRAIBILE

leva lunga tipo FLORA
attacchi ø 3/8"Fx400 mm
portata 13 L/min a 3 bar
pressione max 5 bar
dima di foratura ø 40 mm

SINGLE-HOLE MIXER EXTRACTABLE SHOWER


long lever FLORA
flow rate 13 l/min.a 3 bar
fittings 3/8"F X 400 mm
max pressure 5 bar
mounting hole 40 mm

EINLOCH-MISCHBATTERIE DUSCHE HERAUSZIEH.

Hebel gross FLORA
Wasserdurchfluss 13 L/Min. mit 3 Bar
Anschlüsse 3/8"F x 400 mm
Max Druck 5 Bar
Einbaumass 40 mm

MEZCLADOR 1 AGUJERO DUCHA EXTRAIBLE

palanca larga FLORA
caudal 13 l/min. 3 bar
conexiones 3/8"F X 400 mm
presión max 5 bar
plantilla de perforación 40 mm



3259037

MISCELATORE MONOFORO DOCCIA ESTRAIBILE

leva clinica mini colore nero
attacchi ø 3/8"Fx400 mm
portata 13 L/min a 3 bar
pressione max 5 bar
dima di foratura ø 40 mm

SINGLE-HOLE MIXER EXTRACTABLE SHOWER

black clinic lever
flow rate 13 l/min.a 3 bar
fittings 3/8"F X 400 mm
max pressure 5 bar
mounting hole 40 mm

EINLOCH-MISCHBATTERIE DUSCHE HERAUSZIEH.

Klinikhebel schwarz
Wasserdurchfluss 13 L/Min. mit 3 Bar
Anschlüsse 3/8"F x 400 mm
Max Druck 5 Bar
Einbaumass 40 mm

MEZCLADOR 1 AGUJERO DUCHA EXTRAIBLE

palanca clinica negra
caudal 13 l/min. 3 bar
conexiones 3/8"F X 400 mm
presión max 5 bar
plantilla de perforación 40 mm



3259038

MISCELATORE MONOFORO INCLINATO A LEVA

leva corta tipo EDEN
canna ø 24x300 mm
attacchi ø 3/8"Fx400 mm
portata 16 L/min a 3 bar
pressione max 5 bar
dima di foratura ø 32 mm

SLANTED SINGLE-HOLE MIXER WITH LEVER

short lever EDEN
spout ø 24 x 300 mm
fittings 3/8"F X 400 mm
flow rate 16 l/min.a 3 bar
max pressure 5 bar
mounting hole 34 mm


EINLOCH-MISCHBATTERIE MIT HEBEL GENEIGT

Hebel klein EDEN
Auslaufrohr ø 24 x 300 mm
Asclüsse ø 3/8" F x 400 mm
Fördermenge 16 L/Min. mit 3 bar
Max Druck 5 bar
Einbaumass 34 mm

MEZCLADOR 1 AGUJERO INCLINADO C/PALANCA

palanca corta EDEN
caño ø 24 x 300 mm
conexiones 3/8"F X 400 mm
caudal 16 l/min.a 3 bar
presión max 5 bar
plantilla de perforación 34 mm





3259039

MISCELATORE MONOFORO INCLINATO A LEVA

leva lunga tipo FLORA
canna ø 24x300 mm
attacchi ø 3/8"Fx400 mm
portata 18 L/min a 3 bar
pressione max 5 bar
dima di foratura ø 32 mm

SLANTED SINGLE-HOLE MIXER WITH LEVER

short lever FLORA
spout ø 24 x 300 mm
fittings 3/8"F X 400 mm
flow rate 18 l/min.a 3 bar
max pressure 5 bar
mounting hole 34 mm


EINLOCH-MISCHBATTERIE MIT HEBEL GENEIGT

Hebel gross FLORA
Auslaufrohr ø 24 x 300 mm
Asclüsse ø 3/8" F x 400 mm
Fördermenge 18 L/Min. mit 3 bar
Max Druck 5 bar
Einbaumass 34 mm

MEZCLADOR 1 AGUJERO INCLINADO C/PALANCA

palanca larga FLORA
caño ø 24 x 300 mm
conexiones 3/8"F X 400 mm
caudal 18 l/min.a 3 bar
presión max 5 bar
plantilla de perforación 34 mm





3259030

MISCELATORE BIFORO MONOCOMANDO A LEVA

canna erogazione ø 22x250 mm
attacchi ø 1/2"MM
interasse fori 155 mm
portata 20 L/min a 3 bar
dima di foratura ø 22 mm

TWO-HOLE SINGLE LEVER MIXER

spout 250 mm
black lever 310 mm
distance between holes 155 mm
connections ø 1/2"
mounting hole ø 22 mm


ZWEILÖCHER-MISCHBATTERIE EINHEBEL

Auslaufrohr 250 mm
Hebel schwarz 310 mm
Lochabstand 155 mm
Anschlüsse ø 1/2"
Einbaumass ø 22 mm

MEZCLADOR 2 AGUJEROS MONOMANDO C/PALANCA

caño erogación 250 mm
palanca negra 310 mm
distancia ejes agujeros 155 mm
conexiones ø 1/2"
plantilla de perforación ø 22 mm





3259040

MISCELATORE MONOFORO INCLINATO A LEVA

leva corta tipo EDEN
canna ø 24x200 mm
attacchi ø 3/8"Fx400 mm
portata 18 L/min a 3 bar
pressione max 5 bar
dima di foratura ø 32 mm

SLANTED SINGLE-HOLE MIXER WITH LEVER

short lever EDEN
spout ø 24 x 200 mm
fittings 3/8"F X 400 mm
flow rate 18 l/min.a 3 bar
max pressure 5 bar
mounting hole 34 mm


EINLOCH-MISCHBATTERIE MIT HEBEL GENEIGT

Hebel klein EDEN
Auslaufrohr ø 24 x 200 mm
Asclüsse ø 3/8" F x 400 mm
Fördermenge 18 L/Min. mit 3 bar
Max Druck 5 bar
Einbaumass 34 mm

MEZCLADOR 1 AGUJERO INCLINADO C/PALANCA

palanca corta EDEN
caño ø 24 x 200 mm
conexiones 3/8"F X 400 mm
caudal 18 l/min.a 3 bar
presión max 5 bar
plantilla de perforación 34 mm





3759338

MISCELATORE MONOFORO ECO

canna erogazione a U ø 18x250 mm
attacchi ø 3/8"F x 400 mm
portata 17 L/min a 3 bar
dima di foratura 30 mm
pressione max 5 bar

ONE HOLE MIXER ECO

U shaped spout ø 18x250 mm
fittings ø 3/8"F x 400 mm
flow rate 17 L/min by 3 bar
mounting distance ø 30 mm
max pressure 5 bar


EINLOCH-MISCHBATTERIE ECO

U-Auslaufrohr ø 18x250 mm
Anschlüsse ø 3/8"F x 400 mm
Fördermenge 17 L/min 3 bar
Einbaumass 30 mm
Druck max 5 bar

MEZCLADOR 1 AGUJERO ECO

caño erogación a U ø 18x250 mm
conexiones ø 3/8"F x 400 mm
caudal 17 L/min a 3 bar
plantilla de perforación 30 mm
presión max 5 bar





3759336

MISCELATORE MONOFORO OMEGA

canna erogazione ø 18x250 mm
portata 20 L/min a 3 bar
attacchi ø 3/8"F x 400 mm
dima diforatura ø 30 mm
pressione max 5 bar

ONE HOLE MIXER OMEGA

spout ø 18x250 mm
flow rate 20 L/min by 3 bar
fittings ø 3/8"F x 400 mm
mounting hole ø 30 mm
max pressure 5 bar


EINLOCH-MISCHBATTERIE OMEGA

Auslaufrohr ø 18x250 mm
Fördermenge 20 L/min 3 bar
Anschlüsse ø 3/8"F x 400 mm
Einbaumass ø 30 mm
Druck max 5 bar

MEZCLADOR 1 AGUJERO OMEGA

caño erogación ø 18x250 mm
caudal 20 L/min a 3 bar
conexiones ø 3/8"F x 400 mm
plantilla de perforación ø 30 mm
presión max 5 bar





3759335

MISCELATORE MONOFORO A LEVA 1/4" DI GIRO

canna erogazione a U ø 18x250 mm
attacchi ø 3/8"F x 400 mm
portata 17 L/min a 3 bar
dima di foratura ø 30 mm
pressione max 5 bar

ONE HOLE MIXER WITH LEVER 1/4" TURN

U shaped spout ø 18x250 mm
fittings ø 3/8"F x 400 mm
flow rate 17 l/min a 3 bar
mounting hole ø 30 mm
max pressure 5 bar


EINLOCH-MISCHBATTERIE ECO 1/4" UMDREHUNG

U-Auslaufrohr ø 18x250 mm
Anschlüsse ø 3/8"F x 400 mm
Fördermenge 17 L/min 3 bar
Einbaumass ø 30 mm
Druck max 5 bar

MEZCLADOR 1 AGUJ. PALANCA 1/4" DE VUELTA

caño erogación a U ø 18x250 mm
conexiones ø 3/8"F x 400 mm
caudal 17 L/min a 3 bar
plantilla de perforación ø 30 mm
presión max 5 bar





3759317

MISCELATORE BIFORO DA BANCO 1/4 DI GIRO

canna erogazione ø 18x250 mm
portata 20 L/min a 3 bar
interasse 160 mm
attacchi ø 1/2"MM
dima di foratura ø 22 mm

TWO-HOLE BENCH MIXER 1/4 TURN

spout ø 18x250 mm
flow rate 20 L/min by 3 bar
mounting distance 160 mm
fittings ø 1/2"MM
mounting hole ø 22 mm


ZWEILÖCHER-TISCHMIS-CHBATTERIE 1/4 UMDR.

Auslaufrohr ø 18x250 mm
Fördermenge 20 L/min 3 bar
Achsabstand 160 mm
Anschlüsse ø 1/2"MM
Einbaumass ø 22 mm

MEZCLADOR 2 AGUJ. P. BANCO 1/4 DE VUELTA

caño erogación ø 18x250 mm
caudal 20 L/min a 3 bar
distancia entre ejes 160 mm
conexiones ø 1/2"MM
plantilla de perforación ø 22 mm





3759318

MISCELATORE BIFORO DA BANCO 1/4 DI GIRO

canna erogazione ø 18x250 mm
portata 20 L/min a 3 bar
interasse 160 mm
attacchi ø 3/4"
dima di foratura ø 27 mm

TWO-HOLE BENCH MIXER 1/4 TURN

spout ø 18x250 mm
flow rate 20 L/min by 3 bar
mounting distance 160 mm
fittings ø 3/4"
mounting hole min ø 27 mm


ZWEILÖCHER-TISCHMIS-CHBATTERIE 1/4 UMDR.

Auslaufrohr ø 18x250 mm
Fördermenge 20 L/min 3 bar
Achsabstand 160 mm
Anschlüsse ø 3/4"
Einbaumass ø 27 mm

MEZCLADOR 2 AGUJ. P. BANCO 1/4 DE VUELTA

caño erogación ø 18x250 mm
caudal 20 L/min a 3 bar
distancia entre ejes 160 mm
conexiones ø 3/4"
plantilla de perforación ø 27 mm





3759319

MISCELATORE BIFORO DA BANCO 1/4 DI GIRO

canna erogazione ø 18x300 mm
portata 20 L/min a 3 bar
interasse 160 mm
attacchi ø 3/4"MM
dima di foratura ø 27 mm

TWO-HOLE BENCH MIXER 1/4 TURN

spout ø 18x300 mm
flow rate 20 L/min by 3 bar
mounting distance 160 mm
fittings ø 3/4"MM
mounting hole min ø 27 mm


ZWEILÖCHER-TISCHMIS-CHBATTERIE 1/4 UMDR.

Auslaufrohr ø 18x300 mm
Fördermenge 20 L/min 3 bar
Achsabstand 160 mm
Anschlüsse ø 3/4"MM
Einbaumass ø 27 mm

MEZCLADOR 2 AGUJ. P. BANCO 1/4 DE VUELTA

caño erogación ø 18x300 mm
caudal 20 L/min a 3 bar
distancia entre ejes 160 mm
conexiones ø 3/4" MM
plantilla de perforación ø 27 mm





3759320

RUBINETTO BIFORO ECO A MURO 1/4" DI GIRO

canna erogazione ø 18x250 mm
portata 20 L/min a 3 bar
interasse 155 mm
attacchi ø 1/2"
dima di foratura ø 22 mm

WALL MOUNTED TWO-HOLE TAP 1/4" TURN

spout ø 18x250 mm
flow rate 20 L/min by 3 bar
mounting distance 155 mm
fittings ø 1/2"
mounting hole ø 22 mm


ZWEILÖCHER-WANDHAHN ECO 1/4" UMDREHUNG

Auslaufrohr ø 18x250 mm
Fördermenge 20 L/min 3 bar
Achsabstand 155 mm
Anschlüsse ø 1/2"
Einbaumass ø 22 mm

GRIFO 2 AGUJEROS DE PARED 1/4" DE REV.

caño de erogación ø 18x250 mm
caudal 20 L/min a 3 bar
ditancia entre ejes 155 mm
conexiones ø 1/2"
plantilla de perforación ø 22 mm





3759321

RUBINETTO BIFORO ECO A MURO 1/4" DI GIRO

canna erogazione ø 18x250 mm
portata 20 L/min a 3 bar
interasse 155 mm
attacchi ø 1/2"
dima di foratura ø 22 mm

WALL MOUNTED TWO-HOLE TAP 1/4" TURN

spout ø 18x250 mm
flow rate 20 L/min by 3 bar
mounting distance 155 mm
fittings ø 1/2"
mounting hole ø 22 mm

ZWEILÖCHER-WANDHAHN ECO 1/4" UMDREHUNG

Auslaufrohr ø 18x250 mm
Fördermenge 20 L/min 3 bar
Achsabstand 155 mm
Anschlüsse ø 1/2"
Einbaumass ø 22 mm

GRIFO 2 AGUJEROS DE PARED 1/4" DE REV.

caño de erogación ø 18x250 mm
caudal 20 L/min a 3 bar
ditancia entre ejes 155 mm
conexiones ø 1/2"
plantilla de perforación ø 22 mm



Distributing Components, Spare Parts & Accessories in original quality worldwide

LF SpA HEADQUARTERS
via Voltri, 80 - 47522 Cesena (FC) ITALY
Tel. +39 0547 34 11 11 - Fax +39 0547 34 11 10
www.lfricambi724.it - info@lfricambi.it
Export Dept.: Tel. +39 0547 34 11 50 - Fax: +39 0547 34 11 55
www.lfspareparts724.com - export@lfspareparts.com

LF SpA HOUSEHOLD COMPONENTS DIVISION
Via Padriciano, 99 - AREA Science Park - 34149 Trieste (TS) ITALY
Tel. +39 0547 34 12 42 - Fax +39 0547 34 12 48
www.lfspareparts724.com - info@lfspareparts.com

EPGC Sas FRANCE
13, Rue des Forts - 59960 Neuville en Ferrain
Tel. +33 (0)3 20 25 06 21 - Fax +33 (0)3 20 25 34 12
www.epgc.com - epgc@epgc.com

LF GmbH GERMANY
Junkersstrasse, 3 - D-82178 Puchheim - München
Tel. +49 89 89 45 78 66 - Fax +49 89 89 45 78 88
www.lfersatzteile724.de - info@lfersatzteile.de

LF China REPUBLIC OF CHINA
Room 403, No.2, Huadu Mansion, Lane 422, Huanghua Rd.
Minhang Dist. - 201103 Shanghai
Tel. +86 (0)21 33 53 66 31 - Fax +86 (0)21 33 53 66 32
www.lfspareparts724.com - china@lfspareparts.com

OOO LF RUSSIAN FEDERATION
Ul. Anatoliya Zhivova, 8 - office 1 - 123100 Moscow
Tel./Fax +7 495 725 26 53
www.lfspareparts724.ru - info@lfspareparts.ru

LF Repuestos Horeca S.L.U. SPAIN
Polígono Industrial Carpetania - C/Miguel Faraday, 8 - 28906 Getafe
Tel. +34 91 477 91 00 - Fax +34 91 477 90 81
www.lfrepuestos-horeca724.es - info@lfrepuestos.es

LF Scandinavia Aps - LF Spareparts S.p.A. DENMARK
Nupark, 51 - 7500 Holstebro
Tel. +45 70 70 77 33
www.lfspareparts724.dk - denmark@lfspareparts.dk

LF SpA Cesena (IT) Swiss Branch Steinhausen SWITZERLAND
Sennweidstrasse, 45 - CH-6312 Steinhausen
Tel. +41 (0)41 760 15 80/1 - Fax +41 (0)41 760 15 85
www.lfersatzteile724.ch - info@lfersatzteile.ch

LF Spare Parts Ltd. UNITED KINGDOM
A10a Lakeside Business Park, Broadway Lane
South Cerney, Gloucestershire GL7 5XL
Tel. +44 (0)1285 86 16 25 - Fax +44 (0)1285 86 39 49
www.lfspareparts724.co.uk - info@lfspareparts.co.uk

LF Central East Europe s.r.o. CZECH REPUBLIC
V dolině 1533/1d
100 00, Praha 10
Tel.: +420 730 156 910
www.lfspareparts724.cz - info@lfspareparts.cz

AUSTRALIA AND NEW ZEALAND
www.lfspareparts724.com
andrea.calvio@lfspareparts.com

AUSTRIA
www.lfersatzteile724.at
info@lfersatzteile.at

BALKAN COUNTRIES
www.lfspareparts724.com
matija.ramov@lfspareparts.com

BALTIC COUNTRIES
www.lfspareparts724.com
inara.silina@lfspareparts.com

POLAND
www.lfspareparts724.pl
info@lfspareparts.pl

SOUTH KOREA
www.lfspareparts724.com
fabio.doni@lfspareparts.com

TURKEY
www.lfyedekparca724.com
export@lfspareparts.com

USA AND CANADA
www.lfspareparts724.us
info@lfspareparts.us